





Azienda certificata
SGS ISO 9001/2000

ΔΙΗΛΕΚΤΡΙΚΗ ΤΑΙΝΙΑ ΜΟΝΩΣΗΣ

TECHNICAL DATA SHEET

DIELECTRIC TAPE



DESCRIPTION: dielectric adhesive tape with PVC support of different thicknesses. Self-extinguishing product.

Adhesive:	Natural rubber
Total thickness:	0.13 mm – 0.15 mm – 0.18 mm
Liner:	absent
Peel adhesion to steel:	350 g/cmq
Rolling ball test (P.S.T.C. no 6):	6,5 mm
Temperature resistance:	- 20 °C + 80 °C
Tensile strength at break:	3,3 kg/cm of width
Elongation at break:	150%
Dielectric rigidity:	8000 V
Insulating Class:	Y
Resistance to UV rays:	excellent

MAIN APPLICATIONS: self-extinguishing plastic PVC insulating mono-adhesive tape black or grey, with a total thickness of 0.13 mm - 0.15 mm - 0.18 mm and adhesive mass based of natural rubber. Suitable for taping of electric materials, rebuilding of dielectric joints in cable couplings, mains or pipe quilt, insulation and phase identification, repairs to be carried out by motor vehicle electricians, wiring harness, external turn protective winding of coils, corrosion proofing and mechanical protection windup.

TECNOGAS srl

35020 Albignasego (Padova) ITALY – Viale L. Da Zara, 10 – Tel +39 049 8625910 – Fax +39 049 8625911
www.tecnogas.net – info@tecnogas.net – P.IVA 03859580288 – CCIAA 343104 – Cap. Soc. 500.000,00 € i.v.