

# KLINGER<sup>®</sup>flon Sealant Tape KF-450

Type **S** and Type N

## ΣΤΕΓΑΝΟΠΟΙΗΤΙΚΟ ΣΠΕΙΡΩΜΑΤΩΝ

### **Product description**

KLINGER<sup>®</sup>flon Sealant Tape serves to seal screw joint unions of all kinds and is manufactured of unsintered and degreased PTFE KLINGER<sup>®</sup>flon.

### **Delivery form:**

Form of is supplied on handy plastic reels in 12 m lengths in a width 12 mm approx.

Gauge of tape:

**0.10 mm = Type S**  
**with DVGW-approval**

Gauge of tape:

0.08 mm = Type N  
without DVGW-approval

Temperature resistance

From -196 °C to +250 °C

### **Order example:**

100 reels of KLINGER<sup>®</sup>flon Sealant Tape Type S.



### **Application**

KLINGER<sup>®</sup>flon Sealant Tape has been shown in provide durable service for the reliable, clean and timesaving sealing of fittings and appliances against the leakage of fluids, vapours and gases since many years.

The slackening of all treated screwed joints is easily possible after many of service.

The tape will not swell nor become sticky. It is resistant chemically to all chemical agents (but not against fluorine and melted alkaline metals).

Application is simple and easy. The tape is wrapped around a screw or bolt thread with slight tension and little overlapping. The counterpart is then applied and tightened as usual. One or more layers may be required dependent on the thread pitch.