ΣΩΛΗΝΟΚΟΠΤΕΣ ΧΑΛΚΟΥ–ΙΝΟΧ

Tubing cutters

REMS RAS Cu-INOX for tubes Ø 3-35 mm, 1/8-13/8" REMS RAS Cu-INOX for tubes Ø 3-42 mm, 1/8-13/4"

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by

Retractable internal reamer, pivoted, for automatic alignment to the work piece.

Specially hardened and specially ground reamer blade, replaceable.





Supply format

REMS RAS Cu-INOX. Tubing cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In pressure-sealed plastic bag.

Description	Tubes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.	
Cu-INOX 3-35	3-35 1/8-1 ³ /8"	4	113350	
Cu-INOX 3-42	3-42 1/8-1 ³ /4"	4	113330	



REMS RAS Cu-INOX for tubes Ø 3-28 mm, ¹/₈-1¹/₈" REMS RAS Cu-INOX for tubes Ø 6-42 mm, ¹/₄-1⁵/₈" REMS RAS Cu-INOX for tubes \emptyset 6-64 mm, $^{1}/_{4}$ - $2^{1}/_{2}$ " REMS RAS Cu-INOX for tubes Ø 64-120 mm, 2¹/₂-4"

Robust, solid design for heavy-duty application.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for working capacity Ø 3-120 mm.



Supply format

REMS RAS Cu-INOX. Tubing cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In pressure-sealed plastic bag / cardboard box

in procedio ocalea plactic bag / caraboara box.						
Description	Tubes Ø mm/inch	Wall thickness s ≤ mm	ArtNo.			
Cu-INOX 3-28	3-28 1/8-11/8"	4	113300			
Cu-INOX 6-42	6-42 1/4-1 ⁵ /8"	4	113380			
Cu-INOX 6-64	6-64 1/4-21/2"	4	113400			
Cu-INOX 64-120	64-120 2 ¹ / ₂ -4"	4	113500			

Description	Wall thickness s ≤ mm	ArtNo.
REMS cutter wheel Cu-INOX 3-120, s 4	4	113210

